

Größentabelle freistehender Doppelmembrangasspeicher

VOLUMEN	Ø	Ø AN KLEMMUNG	HÖHE	BETRIEBS-DRUCK
m ³	m	m	m	mbar
55	4,90	4,30	3,70	70,00
75	5,50	4,80	4,10	62,00
105	6,10	5,30	4,60	56,00
135	6,80	5,90	5,10	51,00
180	7,40	6,40	5,50	46,00
215	8,00	6,90	6,00	43,00
280	8,60	7,40	6,50	40,00
345	9,20	8,00	6,90	37,00
415	9,80	8,50	7,40	35,00
495	10,40	9,00	7,80	33,00
590	11,10	9,60	8,30	31,00
690	11,70	10,10	8,70	29,00
795	12,60	10,90	9,50	28,00
1.050	13,40	11,60	10,10	25,00
1.210	14,20	12,30	10,70	24,00
1.365	15,00	13,00	11,20	23,00
1.555	15,80	13,70	11,80	21,00
1.965	16,60	14,40	12,40	20,00
2.175	17,20	14,90	12,90	20,00
2.435	18,10	15,70	13,60	19,00
2.660	18,90	16,40	14,20	18,00
3.235	19,70	17,00	14,70	17,00
3.535	20,40	17,70	15,30	16,00
3.885	21,10	18,30	15,90	16,00
4.615	22,00	19,10	16,50	15,00
4.995	22,80	19,70	17,10	15,00
5.435	23,50	20,30	17,60	14,00
6.210	24,10	20,80	18,20	14,00
6.920	25,00	21,50	18,90	14,00
7.685	26,40	22,60	19,80	13,00
8.525	27,20	23,50	20,40	12,00
9.420	27,90	24,10	20,90	10,00
10.300	28,60	24,80	21,40	9,00